



# Aviation Spark Plugs and Oil Filters



U.S. AIRCRAFT & ENGINES Most generally used plugs shown in Red Type. Plug Listings Taken from FAA Approved Data	Plugs Per Eng.	MASSIVE ELECTRODE				FINE WIRE				OIL FILTER
		Shielded								
		3/4"-20	5/8"-24	3/4"-20	5/8"-24	3/4"-20	5/8"-24	3/4"-20	5/8"-24	
<b>AERONCA</b>										
<b>78C</b> C85-12 (85 h.p.)	8	RHM40E	REM37BY REMA40E	RHM38S	REM38S					
<b>76C</b> C90-12F (95 h.p.)	8	RHM40E	REM37BY REMA40E	RHM38S	REM38S					
<b>150C</b> Cont. C145 (145 h.p.)	12		REM37BY REMA40E	RHM38S	REM38S					
<b>S15AC</b> Frank. 6A4-165-B3 (165 h.p.)	12	RHM40E	REJ38							
<b>11AC Chief</b> Cont. A-65-8 (65 h.p.)	8	RHM40E	REM37BY REMA40E							
<b>11CC Super Chief</b> Cont. C85-12 (85 h.p.)	8	RHM40E	REM37BY REMA40E	RHM38S	REM38S					

U.S. AIRCRAFT & ENGINES Most generally used plugs shown in Red Type. Plug Listings Taken from FAA Approved Data	Plugs Per Eng.	MASSIVE ELECTRODE				FINE WIRE				OIL FILTER
		Shielded								
		3/4"-20	5/8"-24	3/4"-20	5/8"-24	3/4"-20	5/8"-24	3/4"-20	5/8"-24	
<b>AEROSPATIALE (SOCATA)</b>										
<b>T89 Tampico</b> Lyco. 0-320-D2A (160 h.p.)	8		REM37BY REMA40E RHM38E		RHM38S				CH48110-1 CFO-100-1	
<b>TB10 Tobago</b> Lyco. 0-360-A1AD (180 h.p.)	8	RHM40E RHM38E	REM37BY REMA40E RHM38E	RHM38S	REM38S				CH48103-1 CFO-100-1	
<b>TB20 Trinidad</b> Lyco. 0-540-CA5D (200 h.p.)	12	RHM40E RHM38E	REM37BY REMA40E RHM38E	RHM38S	REM38S				CH48103-1 CFO-100-1	
<b>TB21 Trinidad TC</b> Lyco. T10-540-ABAD (250 h.p.)	12	RHB37E RHB32E	RHB37E RHB32E	RHB36S					CH48103-1 CFO-100-1	
<b>TB30</b> Lyco. AE10-540-L1B5D (300 h.p.)	12	RHM38E	REM38E	RHM38S	REM38S				CH48103-1 CFO-100-1	

U.S. AIRCRAFT & ENGINES Most generally used plugs shown in Red Type. Plug Listings Taken from FAA Approved Data	Plugs Per Eng.	MASSIVE ELECTRODE				FINE WIRE				OIL FILTER
		Shielded								
		3/4"-20	5/8"-24	3/4"-20	5/8"-24	3/4"-20	5/8"-24	3/4"-20	5/8"-24	
<b>AG AIRCRAFT (Misc.)</b>										
<b>Air Tractor AT-301/AT301A</b> AT401/AT501 P&W R-1340 (600 h.p.)	18	RHM40E	REM40E REM37BY	RHM38S	REM38S					
<b>Eagle 220</b> Cont. W-670 (220 h.p.)	14	RHM40E	REM40E	RHM38S	REM38S					
<b>Eagle 300</b> Lyco. 0-540-M1B5D (300 h.p.)	18	RHB32E RHB37E	RHB32E RHB37E	RHB32S RHB36S					CH48109-1 CFO-100-1	
<b>Pezelet PZL M-18A Bromader</b> PZL-ASC-212R (1000 h.p.)	18	RHB37E	REB37E	RHB36S					CH48110-1 CFO-100-1	
<b>Pezelet M-21 Bromader Mini</b> PZL-3R (600 h.p.)	14	RHB37E	REB37E	RHB36S					CH48110-1 CFO-100-1	
<b>Thrush SZR, S2D</b> P & W R-1340 (600 h.p.)	18	RHM40E	REM40E	RHM38S	REM38S					
<b>Thrush SZR-800</b> Wright R-1300 (800 h.p.)	14	RHB37E	REB37E	RHB36S					CH48110-1 CFO-100-1	
<b>Schwitzer</b> AG-Cat G164 Cont. W-670 (230 h.p.) Jacobs R755 (275 h.p.)	14	RHM40E	REM40E	RHM38S	REM38S					
<b>Schwitzer</b> Super AG-Cat G164A, B, C P & W R-985 (450 h.p.) P & W R-1340 (600 h.p.)	18	RHM40E	REM37BY REM40E	RHM38S	REM38S					
<b>Weatherly 620</b> P & W R-985 (450 h.p.)	18	RHM40E	REM40E	RHM38S	REM38S					

U.S. AIRCRAFT & ENGINES Most generally used plugs shown in Red Type. Plug Listings Taken from FAA Approved Data	Plugs Per Eng.	MASSIVE ELECTRODE				FINE WIRE				OIL FILTER
		Shielded								
		3/4"-20	5/8"-24	3/4"-20	5/8"-24	3/4"-20	5/8"-24	3/4"-20	5/8"-24	
<b>AMERICAN</b>										
<b>AA-1A, AA-1B Trainer</b> Lyco. 0-235 (108 h.p.)	8	RHM40E	REM40E	RHM38S	REM38S				CH48110-1	
<b>AA-1B, TR2</b> Lyco. 0-235 (108 h.p.)	8	RHM40E	REM40E	RHM38S	REM38S					
<b>AA1C Lyco, T-Cat</b> Lyco. 0-235-L (115 h.p.)	8	RHM40E RHM38E	REM37BY REMA40E	RHM38S	REM38S				CH48110-1 CFO-100-1	
<b>AA-5 Traveler</b> Lyco. 0-420-E (150 h.p.)	8	RHM40E	REM37BY REMA40E	RHM38S	REM38S				CH48110-1 CFO-100-1	
<b>AASA Cheatal</b> Lyco. 0-320-E (150 h.p.)	8	RHM40E	REM37BY REMA40E	RHM38S	REM38S				CH48110-1 CFO-100-1	
<b>AA-5B Tiger</b> Lyco. 0-360-AAK (180 h.p.)	8	RHM40E RHM38E	REM37BY REMA40E	RHM38S	REM38S				CH48110-1 CFO-100-1	
<b>Cougar</b> Lyco. 0-320-D (160 h.p.)	8	RHM40E RHM38E	REM37BY REMA40E	RHM38S	REM38S				CH48110-1 CFO-100-1	

U.S. AIRCRAFT & ENGINES Most generally used plugs shown in Red Type. Plug Listings Taken from FAA Approved Data	Plugs Per Eng.	MASSIVE ELECTRODE				FINE WIRE				OIL FILTER
		Shielded								
		3/4"-20	5/8"-24	3/4"-20	5/8"-24	3/4"-20	5/8"-24	3/4"-20	5/8"-24	
<b>BEECH</b>										
<b>D-17S</b> P&W R-985-AN (450 h.p.)	18	RHM40E	REM37BY REMA40E	RHM38S	REM38S					
<b>D16S, E16S, G16S, H16S, AT11</b> 21P&W R-985-AN (450 h.p.)	18	RHM40E	REM37BY REMA40E	RHM38S	REM38S					
<b>Bonanza E33</b> Cont. 0-470-K (225 h.p.)	12	RHM40E	REM40E	RHM38S	REM38S					
<b>E33A, F33A, F33B, F33C</b> Lyco. 0-520-B (285 h.p.)	12	RHB32E	RHB32E	RHB36S RHB32S					CH48109-1	
<b>Bonanza A35, B35</b> Cont. E-185 (185 h.p.)	12	RHM40E	REM40E	RHB36S	REM38S					
<b>C35, D35, E35, F35</b> Cont. E-185-11 (205 h.p.)	12	RHM40E	REM40E	RHM38S	REM38S					
<b>G35</b> Cont. E-225-8 (225 h.p.)	12		REM40E							
<b>H35</b> Cont. 0-470-G (240 h.p.)	12	RHM40E RHM38E	REM40E REMA40E	RHM38S	REM38S				CH48108-1 CFO-100-1	
<b>J35, K35, M35</b> Cont. 0-470-G (240 h.p.)	12	RHM40E RHM38E	REM40E REMA40E	RHM38S	REM38S				CH48108-1 CFO-100-1	
<b>N35, P35, G33</b> Cont. 0-470-N (260 h.p.)	12	RHB32E	RHB32E	RHB36S RHB32S					CH48108-1 CFO-100-1	
<b>S-35, V-35, V35A, V35B</b> Cont. 0-520-B (285 h.p.)	12	RHB32E	RHB32E	RHB36S RHB32S					CH48109-1	
<b>V35TC, V35A-TC, V35B-TC</b> Cont. 0-520-C (285 h.p.)	12	RHB32E	RHB32E	RHB36S RHB32S					CH48109-1	
<b>36, A36</b> Cont. 0-520-B (285 h.p.)	12	RHB32E	RHB32E	RHB36S RHB32S					CH48109-1	
<b>A36TC, B36TC</b> Cont. T30-520-UB (300 h.p.)	12	RHB32E	RHB32E	RHB32S					CH48109-1	
<b>36B</b> Cont. 0-550-B (300 h.p.)	12	RHB32E	RHB32E	RHB36S					CH48108-1	
<b>G36 Bonanza</b> Cont. 0-550-B (300 h.p.)	12	RHB32E	RHB32E	RHB36S					CH48109-1	
<b>C50</b> 2/Lyco. G0-480-F (275 h.p.)	12	RHM40E RHM38E	REM40E REMA40E	RHM38S	REM38S					
<b>D50, D50A</b> 1/2" Rch. Cyl. 2/Lyco. G0-480-C, G (295 h.p.)	12	RHM38E	REM38E	RHM38S	REM38S				REM38S	
<b>D50, D50A</b> 13/16" Rch. Cyl. 2/Lyco. G0-480-G, C (295 h.p.)	12	RHB37E	RHB36S							
<b>E50, F50</b> 1/2" Rch. Cyl. 2/Lyco. G50-480-A, -B (340 h.p.)	12	RHM38E	REM38E	RHM38S	REM38S				REM38S	
<b>E50, F50</b> 13/16" Rch. Cyl. 2/Lyco. G50-480-A, -B (340 h.p.)	12	RHB37E	RHB36S							
<b>G50, H50, J50</b> 1/2" Rch. Cyl. 2/Lyco. G50-480-A, (340 h.p.)	12	RHM38E	REM38E	RHM38S	REM38S				REM38S	
<b>G50, H50, J50</b> 13/16" Rch. Cyl. 2/Lyco. G50-480-A, (340 h.p.)	12	RHB37E	RHB36S							
<b>Travel Air 85, B95</b> 2/Lyco. 0-360-A (180 h.p.)	8	RHM40E RHM38E	REM40E REMA40E	RHM38S	REM38S				CH48110-1 CFO-100-1	
<b>Travel Air 895A, 895A, E95</b> 2/Lyco. 0-360-B (180 h.p.)	8	RHM40E RHM38E	REM40E REMA40E	RHM38S	REM38S				CH48110-1 CFO-100-1	
<b>Debonair 23, A33</b> Cont. 0-470-J (225 h.p.)	12	RHM40E	REM40E	RHM38S	REM38S					
<b>Debonair B33, C33, D33, E33B</b> Cont. 0-470-K (225 h.p.)	12	RHM40E	REM40E	RHM38S	REM38S					
<b>Debonair C33A, E33A, E33C</b> Cont. 0-520-B (285 h.p.)	12	RHB32E	RHB32E	RHB36S RHB32S					CH48109-1	
<b>Baron 85, A55, B55, B55B</b> 2/Cent. 0-470-L (260 h.p.)	12	RHB32E	RHB32E	RHB36S RHB32S					CH48109-1	
<b>Baron 85, A55, B55, E55</b> 2/Cent. 0-520-C (285 h.p.)	12	RHB32E	RHB32E	RHB36S RHB32S					CH48109-1	
<b>Baron 56TC</b> 2/Lyco. T10-541-E1B4 (380 h.p.)	12	RHB37E RHB32E	RHB37E RHB32E	RHB36S RHB32S					CH48104-1* CFO-101-1	
<b>Baron 56, 58A</b> 2/Cent. 0-520-C, -CB (285 h.p.)	12	RHB32E	RHB32E	RHB36S					CH48109-1	
<b>Baron 58P, 58TC</b> 2/Cent. T30-520-L, -WB (310 h.p.) (325 h.p.)	12	RHB32E	RHB32E	RHB36S RHB32S					CH48109-1 CFO-100-1	
<b>Baron 58C</b> 2/Cent. 0-520-C (300 h.p.)	12	RHB32E	RHB32E	RHB36S RHB32S					CH48108-1	
<b>Baron 65B</b> 2/Cent. 0-520-C (300h.p.)	12	RHB32E	RHB32E	RHB36S					CH48109-1	
<b>Duke 60, A60, B60</b> 2/Lyco. T10-541-E1A4 (380 h.p.)	12	RHB37E RHB32E	RHB37E RHB32E	RHB36S RHB32S					CH48108-1* CFO-101-1	
<b>Queen Air 65, 70</b> 1/2" Rch. Cyl. 2/Lyco. G50-480-A (340 h.p.)	12	RHM38E	REM38E	RHM38S					CH48111 CFO-101-1	
<b>Queen Air 65, 70</b> 13/16" Rch. Cyl. 2/Lyco. G50-480-A (340 h.p.)	12	RHB37E RHB32E	RHB37E RHB32E	RHB36S RHB32S					CH48111 CFO-101-1	
<b>Queen Air 80, 88, 880</b> 2/Lyco. G50-540-A (380 h.p.)	12	RHM40E	REM40E	RHM38S	REM38S				CH48110-1 CFO-101-1	
<b>Muskeeter, Sport III, B19 Sport</b> Lyco. 0-320-A, -E (150 h.p.)	8	RHM40E	REM37BY REMA40E	RHM38S	REM38S				CH48110-1 CFO-101-1	
<b>Muskeeter 23</b> Lyco. 0-320-D2B (160 h.p.)	8	RHM40E	REM40E	RHM38S	REM38S				CH48110-1 CFO-101-1	
<b>Muskeeter A23-19A</b> C23 Sundowner Lyco. 0-360-A (180 h.p.)	8	RHM40E RHM38E	REM37BY REMA40E	RHM38S	REM38S				CH48110-1 CFO-101-1	
<b>Muskeeter A23, 23 Custom III</b> A23A Cont. 0-346-A (165 h.p.)	8	RHM40E RHM38E	REM37BY REMA40E	RHM38S	REM38S				CH48109-1	
<b>24 Super III, A24</b> A24R, B24R, C-24R Sierra Lyco. 0-360	8	RHM38E	REM38E	RHM38S	REM38S				CH48110-1 CFO-101-1	
<b>Duchess 76</b> 2/Lyco. 0-360-E1A6D (180 h.p.)	8	RHM40E RHM38E	REM40E REMA40E	RHM38S	REM38S				CH48103-1*	
<b>Skagger 77</b> Lyco. 0-235-L2C (115 h.p.)	8	RHM38E	REM38E	RHM38S	REM38S				CH48110-1	

U.S. AIRCRAFT & ENGINES Most generally used plugs shown in Red Type. Plug Listings Taken from FAA Approved Data	Plugs Per Eng.	MASSIVE ELECTRODE				FINE WIRE				OIL FILTER
		Shielded								
		3/4"-20	5/8"-24	3/4"-20	5/8"-24	3/4"-20	5/8"-24	3/4"-20	5/8"-24	
<b>BELLANCA</b>										
<b>14-13 Series</b> Frank. 6A4-150 (150 h.p.) 6A4-165 (165 h.p.)	12		REJ38							
<b>14-15</b> <										